


# SUPRAMID

BLACK



<b>Type</b>	Twisted and coated multifilament Sizes 5/0 and 6/0 monofilament
<b>Composition</b>	Polyamide 6.6 strands enclosed in a polyamide 6 sheet
<b>Colour</b>	Black
<b>Tissue reaction</b>	Minimal
<b>Absorption</b>	Non absorbable, gradually encapsulated by connective tissue
<b>Presentation</b>	Box with 12 sutures

*For quality  
&  
safety*

**smi**

[www.sutures.be](http://www.sutures.be)

# SUPRAMID

BLACK



















## **CHARACTERISTICS**











- ✓ High tensile strength, non absorbable
- ✓ Synthetic
- ✓ Twisted structure
  
- ✓ Multifilament in a sheath
  
- ✓ Pliability and softness
  
- ✓ Hermetically sealed packing




**INDICATIONS**    General soft tissue closing  
                                  and/or ligation  
especially in        Skin closure




## **BENEFITS**

- Excellent and permanent tissue support
  
- Minimal tissue reaction
  
- Excellent handling properties  
High flexibility  
High tensile strength  
Excellent knot security
  
- Soft passage through the tissues without sawing,  
tissue drag and trauma  
Good knot tie down / adjustability  
Reduced capillary action
  
- Good handling properties  
Easy and secure knotting
  
- Guaranteed seal and product sterility

Round bodied taper point			Metric	USP	Length	Order number	
1/2 Circle 	HR 16 mm		1.5	4/0	75 cm	<i>black</i> 4150116	
			2	3/0	75 cm	<i>black</i> 4200116	
	HR 20 mm		2	3/0	45 cm	<i>black</i> 4200120	
			HR 26 mm		3	2/0	75 cm
	Round bodied taper point				Metric	USP	Length
	Straight 			GR 22 mm	1.5	4/0	50 cm
Reverse cutting			Metric	USP	Length	Order number	
1/2 Circle 	HS 17 mm		1.5	4/0	75 cm	<i>black</i> 4151417	
			2	3/0	75 cm	<i>black</i> 4201417	
	HS 20 mm		1	5/0	75 cm	<i>black</i> 4101420	
			1.5	4/0	75 cm	<i>black</i> 4151420	
	HS 22 mm		2	3/0	75 cm	<i>black</i> 4201420	
			1.5	4/0	75 cm	<i>black</i> 4151422	
	HS 26 mm		1.5	4/0	75 cm	<i>black</i> 4151426	
			2	3/0	75 cm	<i>black</i> 4201426	
			3	2/0	75 cm	<i>black</i> 4301426	
	Cutting			Metric	USP	Length	Order number
Straight 			GS 20 mm	1.5	4/0	50 cm	<i>black</i> 4152120
			GS 25 mm	1.5	4/0	60 cm	<i>black</i> 4152125

Reverse cutting			Metric	USP	Length	Order number
<b>3/8 Circle</b> 	DS 12 mm		0.7	6/0	75 cm	<i>black</i> 4071512
			1	5/0	75 cm	<i>black</i> 4101512
			1.5	4/0	45 cm	<i>black</i> 4151512
	DS 16 mm		0.7	6/0	75 cm	<i>black</i> 4071516
			1	5/0	75 cm	<i>black</i> 4101516
			1.5	4/0	45 cm	<i>black</i> 4151516
			1.5	4/0	75 cm	<i>black</i> 4151516-75
			2	3/0	45 cm	<i>black</i> 4201516
			2	3/0	75 cm	<i>black</i> 4201516-75
	DS 16 mm black		1	5/0	75 cm	<i>black</i> 4101516VB
	DS 19 mm		0.7	6/0	75 cm	<i>black</i> 4071519
			1	5/0	75 cm	<i>black</i> 4101519
			1.5	4/0	45 cm	<i>black</i> 4151519
			1.5	4/0	75 cm	<i>black</i> 4151519-75
			2	3/0	75 cm	<i>black</i> 4201519
	DS 19 mm Easy Pass		1.5	4/0	75 cm	<i>black</i> 4151519P-75
	DS 19 mm black		1	5/0	75 cm	<i>black</i> 4101519VB
			1.5	4/0	75 cm	<i>black</i> 4151519VB
DS 24 mm		2	3/0	75 cm	<i>black</i> 4201524	
		3	2/0	75 cm	<i>black</i> 4301524	
		3.5	0	75 cm	<i>black</i> 4351524	
DS 36 mm		3	2/0	75 cm	<i>black</i> 4301536	
		3.5	0	75 cm	<i>black</i> 4351536	
		4	1	75 cm	<i>black</i> 4401536	

Round bodied taper cutting point			Metric	USP	Length	Order number
<b>1/2 Circle</b> 	HRT 18 mm		1.5	4/0	75 cm	<i>black</i> 4150518
			2	3/0	75 cm	<i>black</i> 4200518

Round bodied taper cutting point			Metric	USP	Length	Order number
<b>3/8 Circle</b> 	DRT 18 mm		1.5	4/0	75 cm	<i>black</i> 4150418
			2	3/0	75 cm	<i>black</i> 4200418